

	Standard	Result
 Size	EN ISO 24342	See separate table
 Thickness	EN ISO 24346	2.0 mm
 Wear layer	EN ISO 24340	0.3 mm
Surface treatment		PU coating
Warranty¹	Commercial	10 years
	Residential	20 years
 Bevelled edge		No
 Mass per unit area	EN ISO 23997	3605 g/m ²
 Standards	EN ISO 10582	Pass
 Classification	EN ISO 10874 - Commercial	31: Commercial moderate
	EN ISO 10874 - Domestic	23: Domestic heavy
 Reaction to fire	EN 13501-1	B _{fl} -s1
 Staining resistance	EN ISO 26987	Excellent
 Light fastness	EN ISO 105-B02	Pass (≥ 6)
 Abrasion resistance	EN ISO 10582	Type 1
 Flexibility	EN ISO 24344	Pass
 Dimensional stability	EN ISO 23999	Pass (≤ 0.25%)
 Acoustic impact noise reduction	EN ISO 717-2/EN ISO 140-8	ΔL _w = 1 dB
 Electrical behaviour body voltage	EN 1815	Pass
 Indentation - residual	EN ISO 24343-1	Pass (≤ 0.1 mm)
 Castor chair continuous use	ISO 4918	Pass
 Thermal resistance	ISO 8302	0.0084 m ² K/W
		Suitable for underfloor heating. Max 27°C
 Slip resistance²	EN 13893	DS
	EN 16165 Annex B/DIN 51130	R10
 Light Reflectance Value (LRV)	BS 8493:2008+A1:2010	See separate table
 Adhesive	Karndean Universal	Yes
	Silane	Yes
	Pressure Sensitive	Yes
 Environmental	Indoor Air Comfort	Gold certification; Compliant low emitting VOC emissions.
	Floorscore SCS-EC10.3-2014 v4.0	Indoor air quality certified; Compliant low emitting VOC emissions.
	ISO 14001 / ISO 9001	Manufactured to quality and environment management systems standard
 Recycling		Suitable
 Phthalate free		Yes

¹ Subject to terms. Please see our website.

² Slip resistance is measured on freestanding ex-factory product. Slip resistance can be affected by many factors, including but not limited to; product installation and underlayment, surface contamination, use, wear and how the product is maintained. Textural variation along the surface of the product can affect nominal values.

For more information:

UK: 01 386 820110 | ROI: 01 6569887

Email: info@palioflooring.com

Visit: www.palioflooring.com



BS EN 14041: 2004 (DOP 2021/UKCA/PGLuedownv01)
Approved body 0321
Floor coverings (Internal)
ISO 10874 Class 23/31
Manufactured to ISO 10582



EN 14041: 2004 (DOP 2017/PGLuedownvEN02)
Notified body 0483
Floor coverings (Internal)
ISO 10874 Class 23/31
Manufactured to ISO 10582

	Product Code	Size		Box Quantity		Slip Resistance EN 16165 Annex B / DIN 51130	LRV
		mm	inches	m ²	Pieces		
Wood Designs	PVP401	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	41
	PVP402	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	40
	PVP403	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	25
	PVP404	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	15
	PVP405	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	12
	PVP406	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	32
	PVP407	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	30
	PVP408	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	19
	PVP409	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	28
	PVP410	1219.2mm x 177.8mm	48.0" x 7.0"	4.335	20 Planks	R10	28
	SM-PVP401	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	41
	SM-PVP402	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	40
	SM-PVP403	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	25
	SM-PVP404	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	15
	SM-PVP405	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	12
	SM-PVP406	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	32
	SM-PVP407	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	30
	SM-PVP408	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	19
	SM-PVP409	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	28
	SM-PVP410	457.2 x 76.2	18.0" x 3.0"	3.345	96 Planks	R10	28
Stone Designs	PVT701	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	65
	PVT702	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	44
	PVT703	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	42
	PVT704	304.8 x 457.2	12.0" x 18.0"	3.345	24 Tiles	R10	12